



Felandia

General data	
Frame size	100
Housing material	Aluminum
Install model	According to the standard
Type of feet	Removable feet
Net weight	17.2 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) Customizable (Optional)
Rotation direction	Clockwise (Standard) Counter clockwise (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M20× 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.75	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
	400	V Y @ 50Hz
	276	V Δ @ 60Hz
	480	V Y @ 60Hz
Rotation speed	700	RPM @ 50Hz
	840	RPM @ 60Hz
Rated current	3.71	A (In) @ Δ 50Hz
	2.13	A (In) @ Y 50Hz
Starting current	4.4	×In
Rated torque	10.23	Nm (Mn)
Starting torque	2.1	×Mn
Breakdown torque	2.55	×Mn
Efficiency	75.2	IE1 @ 100% load
	74.8	@ 75% load
	70.8	@ 50% load
Power factor cosφ	0.68	@ 100% load

Mechanical data		
Bearings brand	C&U (Standard) Customizable (Optional)	
Bearings type	6206 2RZ C3	(DE) (NDE)
Lifetime of bearings		6206 2RZ C3 hours
Allowed radial load		20000 N
Allowed axial load		1437 N
Grease type		1247
Lubrication interval of NDE bearing		h
Lubrication interval of DE bearing		h
Moment of inertia	0.00604	Kg*m ²
Noise level	59	dB(A)