



Felandia

General data		
Frame size	56	
Housing material	Aluminum	
Install model	According to the standard	
Type of feet	Removable feet	
Net weight	3.2 kg	
Insulation class	F H	(Standard) (Optional)
Protection degree	IP 55 IP 56	(Standard) (Optional)
Thermal protection	Without Customizable	(Standard) (Optional)
Rotation direction	Clockwise Counter clockwise	(Standard) (Optional)
Service duty	S1	
Vibration level	A	
Balance	Half-key balanced	
Cable glands	1 - M16 × 1.5	
Cooling	IC 411	
Painting color	RAL 7024 Customizable	(Standard) (Optional)
Regulations	IEC / DIN / ISO / VDE / EN	
Standard	IEC 60034	

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.09	kW
Frequency	50	Hz
Voltage (±5%)	230 400 276 480	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	1400 1680	RPM @ 50Hz RPM @ 60Hz
Rated current	0.68 0.39	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	3.1	×In
Rated torque	0.61	Nm (Mn)
Starting torque	2.3	×Mn
Breakdown torque	2.5	×Mn
Efficiency	56.2 51.7 43.1	IE1 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.59	@ 100% load

Mechanical data		
Bearings brand	C&U Customizable	(Standard) (Optional)
Bearings type	6201 2RZ C3	(DE) (NDE)
Lifetime of bearings	6201 2RZ C3 hours	
Allowed radial load Allowed axial load	20000 N 413 N	
Grease type	355	
Lubrication interval of NDE bearing Lubrication interval of DE bearing	h h	
Moment of inertia	0.00024	Kg*m ²
Noise level	50	dB(A)