



Felandia

General data	
Frame size	90
Housing material	Aluminum
Install model	According to the standard
Type of feet	Removable feet
Net weight	15.1 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) Customizable (Optional)
Rotation direction	Clockwise (Standard) Counter clockwise (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	1 - M20 × 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	1.1	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
	400	V Y @ 50Hz
	276	V Δ @ 60Hz
	480	V Y @ 60Hz
Rotation speed	1440	RPM @ 50Hz
	1730	RPM @ 60Hz
Rated current	4.42	A (In) @ Δ 50Hz
	2.55	A (In) @ Y 50Hz
Starting current	7.7	×In
Rated torque	7.30	Nm (Mn)
Starting torque	3.7	×Mn
Breakdown torque	3.8	×Mn
Efficiency	84.1	IE3 @ 100% load
	84.1	@ 75% load
	81.8	@ 50% load
Power factor cosφ	0.74	@ 100% load

Mechanical data		
Bearings brand	C&U (Standard) Customizable (Optional)	
Bearings type	6205 2RZ C3 (DE) 6205 2RZ C3 (NDE)	
Lifetime of bearings		20000 hours
Allowed radial load		815.98 N
Allowed axial load		670.72 N
Grease type		
Lubrication interval of NDE bearing		h
Lubrication interval of DE bearing		h
Moment of inertia	0.003841812	Kg*m ²
Noise level	61	dB(A)