



Felandia

General data	
Frame size	100
Housing material	Aluminum
Install model	According to the standard
Type of feet	Removable feet
Net weight	23.9 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) Customizable (Optional)
Rotation direction	Clockwise (Standard) Counter clockwise (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M20 × 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	2.2	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
	400	V Y @ 50Hz
	276	V Δ @ 60Hz
	480	V Y @ 60Hz
Rotation speed	1450	RPM @ 50Hz
	1740	RPM @ 60Hz
Rated current	7.74	A (In) @ Δ 50Hz
	4.47	A (In) @ Y 50Hz
Starting current	8	×In
Rated torque	14.49	Nm (Mn)
Starting torque	2.9	×Mn
Breakdown torque	3.5	×Mn
Efficiency	86.7	IE3 @ 100% load
	87.2	@ 75% load
	86.2	@ 50% load
Power factor cosφ	0.82	@ 100% load

Mechanical data		
Bearings brand	C&U (Standard) Customizable (Optional)	
Bearings type	6206 2RZ C3	(DE)
	6206 2RZ C3	(NDE)
Lifetime of bearings	20000 hours	
Allowed radial load	1141.7 N	
	Allowed axial load	
Grease type		
Lubrication interval of NDE bearing	h	
Lubrication interval of DE bearing	h	
Moment of inertia	0.008754006	Kg*m ²
Noise level	64	dB(A)