



Felandia

General data	
Frame size	280
Housing material	Casting iron
Install model	According to the standard
Type of feet	Removable feet (Standard) <i>Fixed feet</i> (Optional)
Net weight	692 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) <i>Customizable</i> (Optional)
Rotation direction	Clockwise (Standard) <i>Counter clockwise</i> (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M50× 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) <i>Customizable</i> (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	90	kW
Frequency	50	Hz
Voltage (±5%)	400	V Δ @ 50Hz
	690	V Y @ 50Hz
	480	V Δ @ 60Hz
	828	V Y @ 60Hz
Rotation speed	1480	RPM @ 50Hz
	1776	RPM @ 60Hz
Rated current	160.53	A (In) @ Δ 50Hz
	92.68	A (In) @ Y 50Hz
Starting current	10	×In
Rated torque	580.74	Nm (Mn)
Starting torque	2.5	×Mn
Breakdown torque	2.8	×Mn
Efficiency	95.2	IE3 @ 100% load
	95.1	@ 75% load
	95	@ 50% load
Power factor cosφ	0.85	@ 100% load

Mechanical data		
Bearings brand	C&U (Standard) <i>Customizable</i> (Optional)	
Bearings type	6316 C3	(DE)
	6316 C3	(NDE)
Lifetime of bearings		- hours
Allowed radial load		8500 N
Allowed axial load		57700 N
Grease type	polyurea-based grease	
Lubrication interval of NDE bearing		10500 h
Lubrication interval of DE bearing		10500 h
Moment of inertia	2.183450	Kg*m ²
Noise level	86	dB(A)