



Felandia

General data		
Frame size	63	
Housing material	Aluminum	
Install model	According to the standard	
Type of feet	Removable feet	
Net weight	4.5 kg	
Insulation class	F H	(Standard) (Optional)
Protection degree	IP 55 IP 56	(Standard) (Optional)
Thermal protection	Without Customizable	(Standard) (Optional)
Rotation direction	Clockwise Counter clockwise	(Standard) (Optional)
Service duty	S1	
Vibration level	A	
Balance	Half-key balanced	
Cable glands	1 - M18 × 1.5	
Cooling	IC 411	
Painting color	RAL 7024 Customizable	(Standard) (Optional)
Regulations	IEC / DIN / ISO / VDE / EN	
Standard	IEC 60034	

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.18	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
Rotation speed	1340	RPM @ 50Hz
Rated current	1.36	A (In) @ Δ 50Hz
Starting current	4.5	×In
Rated torque	1.28	Nm (Mn)
Starting torque	2.3	×Mn
Breakdown torque	1.43	×Mn
Efficiency	60	- @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.96	@ 100% load

Mechanical data		
Bearings brand	C&U Customizable	(Standard) (Optional)
Bearings type	6201 2RZ C3 6201 2RZ C3	(DE) (NDE)
Lifetime of bearings	20000 hours	
Allowed radial load Allowed axial load	409 N 353 N	
Grease type	-	
Lubrication interval of NDE bearing Lubrication interval of DE bearing	- h - h	
Moment of inertia	0.000340	Kg*m ²
Noise level	65	dB(A)