



# Felandia

General data		
Frame size	58	
Housing material	Aluminum	
Install model	According to the standard	
Type of feet	Removable feet	
Net weight	11.27 kg	
Insulation class	F H	(Standard) (Optional)
Protection degree	IP 55 IP 56	(Standard) (Optional)
Thermal protection	Without Customizable	(Standard) (Optional)
Rotation direction	Clockwise Counter clockwise	(Standard) (Optional)
Service duty	S1	
Vibration level	A	
Balance	Half-key balanced	
Cable glands	1 - M16 × 1.5	
Cooling	IC 411	
Painting color	RAL 7024 Customizable	(Standard) (Optional)
Regulations	IEC / DIN / ISO / VDE / EN	
Standard	IEC 60034	

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	1.5	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
Rotation speed	2790	RPM @ 50Hz
Rated current	9.51	A (In) @ Δ 50Hz
Starting current	5	×In
Rated torque	5.13	Nm (Mn)
Starting torque	0.35	×Mn
Breakdown torque	1.7	×Mn
Efficiency	70	- @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.98	@ 100% load

Mechanical data		
Bearings brand	C&U Customizable	(Standard) (Optional)
Bearings type	6004 2RZ C3 6003 2RZ C3	(DE) (NDE)
Lifetime of bearings	20000 hours	
Allowed radial load	463 N	
Allowed axial load	336 N	
Grease type	-	
Lubrication interval of NDE bearing	- h	
Lubrication interval of DE bearing	- h	
Moment of inertia	0.000900	Kg*m <sup>2</sup>
Noise level	80	dB(A)