



Felandia

MSC/MYC Series

TYPE	Power (kW)	Phase	V	HZ	Amp.	Eff.	Cosφ	Rpm	T _s /T _n	T _m /T _n	I _s /I _n	Duty	Capacitor	Inertia kg* \ddot{m}^2
MYC-581-2	1.1	1	230	50	7.18	68	0.98	2770	0.35	1.7	5	S6-40%	25uF/450V	0.000697
MYC-582-2	1.5	1	230	50	9.51	70	0.98	2790	0.35	1.7	5	S6-40%	30uF/450V	0.000900
MYC-583-2	1.8	1	230	50	11.1	72	0.98	2790	0.32	1.7	5	S6-40%	30uF/450V	0.001031
MYC-632-2	2.2	1	230	50	13.2	74	0.98	2800	0.32	1.7	5	S6-40%	40uF/450V	0.001220
MSC-581-2	1.5	3	400	50	3.41	77.5	0.82	2750	3	3	6	S6-40%		0.000762
MSC-582-2	2.2	3	400	50	4.76	78.5	0.85	2750	3	3	6	S6-40%		0.001031
MSC-631-2	2.2	3	400	50	4.73	79	0.85	2800	2.4	2.2	6	S6-40%		0.001276
MSC-632-2	3	3	400	50	6.37	80	0.85	2820	2.8	2.4	6.5	S6-40%		0.001679
MSC-741-2	4	3	400	50	8.19	82	0.86	2850	3	3	7	S6-40%		0.003118
MSC-811-2	5.5	3	400	50	10.5	85	0.89	2880	3	3	9	S1		0.005452
MSC-812-2	7.5	3	400	50	14.1	86	0.89	2880	3	3	9	S1		0.007185
MSC-931-2	5.5	3	400	50	10.1	87	0.9	2890	3	3	9	S1		0.004694
MSC-932-2	7.5	3	400	50	13.6	87.5	0.91	2890	3	3	9	S1		0.005935