



Felandia

General data	
Frame size	71
Housing material	Aluminum
Install model	According to the standard
Type of feet	Removable feet
Net weight	5.96 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) Customizable (Optional)
Rotation direction	Clockwise (Standard) Counter clockwise (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	1 - M20 × 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.37	kW
Frequency	50	Hz
Voltage (±5%)	230 400 276 480	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	1385 1665	RPM @ 50Hz RPM @ 60Hz
Rated current	1.76 1.02	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	4.3	×In
Rated torque	2.55	Nm (Mn)
Starting torque	2	×Mn
Breakdown torque	2.2	×Mn
Efficiency	70 70.5 66.2	IE1 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.75	@ 100% load

Mechanical data		
Bearings brand	C&U (Standard) Customizable (Optional)	
Bearings type	6202 2RZ C3 (DE) 6202 2RZ C3 (NDE)	
Lifetime of bearings		20000 hours
Allowed radial load		451 N
Allowed axial load		383 N
Grease type		
Lubrication interval of NDE bearing		h
Lubrication interval of DE bearing		h
Moment of inertia	0.000717	Kg*m ²
Noise level	55	dB(A)