


**Felandia**

## Koonuspuksid/ Taper Lock Bushes



DIAMETER	10 TO 12	4	d+1,8
DIAMETER	13 TO 17	5	d+2,3
DIAMETER	18 TO 22	6	d+2,8
DIAMETER	23 TO 30	8	d+3,3
DIAMETER	31 TO 38	10	d+3,3
DIAMETER	39 TO 44	12	d+3,3
DIAMETER	45 TO 50	14	d+3,8
DIAMETER	51 TO 58	16	d+4,3
DIAMETER	59 TO 65	18	d+4,4
DIAMETER	66 TO 75	20	d+4,9
DIAMETER	76 TO 85	22	d+5,4
DIAMETER	86 TO 95	25	d+5,4
DIAMETER	96 TO 110	28	d+6,4
DIAMETER	111 TO 130	32	d+7,4
DIAMETER	131 TO 150	36	d+8,4

## Tootekoodi seletus/ Meaning and Usage

1008	10 ( maximum bore diameter: 1.0" - 25.4mm i.e )	08 ( taper bush height: 0.8" - 20.3mm i.e )
1108	11 ( maximum bore diameter: 1.1" )	08 ( taper bush height: 0.8" )
1210	12 ( maximum bore diameter: 1.2" )	10 ( taper bush height: 1.0" )
1310	13 ( maximum bore diameter: 1.3" )	10 ( taper bush height: 1.0" )
1610	16 ( maximum bore diameter: 1.6" )	10 ( taper bush height: 1.0" )
2012	20 ( maximum bore diameter: 2.0" )	12 ( taper bush height: 1.2" )
2517	25 ( maximum bore diameter: 2.5" )	17 ( taper bush height: 1.7" )
2525	25 ( maximum bore diameter: 2.5" )	25 ( taper bush height: 2.5" )
3020	25 ( maximum bore diameter: 2.5" )	25 ( taper bush height: 2.5" )
3030	30 ( maximum bore diameter: 3.0" )	30 ( taper bush height: 3.0" )
3525	35 ( maximum bore diameter: 3.5" )	25 ( taper bush height: 2.5" )
3535	35 ( maximum bore diameter: 3.5" )	35 ( taper bush height: 3.5" )
4040	40 ( maximum bore diameter: 4.0" )	40 ( taper bush height: 4.0" )
5050	50 ( maximum bore diameter: 5.0" )	50 ( taper bush height: 5.0" )
6050	60 ( maximum bore diameter: 6.0" )	50 ( taper bush height: 5.0" )