



Felandia

General data	
Frame size	63
Housing material	Aluminum
Install model	According to the standard
Type of feet	Removable feet
Net weight	4.1 kg
Insulation class	F H (Standard) (Optional)
Protection degree	IP 55 IP 56 (Standard) (Optional)
Thermal protection	Without Customizable (Standard) (Optional)
Rotation direction	Clockwise Counter clockwise (Standard) (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	1 - M16 × 1.5
Cooling	IC 411
Painting color	RAL 7024 Customizable (Standard) (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.25	kW
Frequency	50	Hz
Voltage (±5%)	230 400 276 480	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	2840 3400	RPM @ 50Hz RPM @ 60Hz
Rated current	1.18 0.68	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	5.2	×In
Rated torque	0.84	Nm (Mn)
Starting torque	2.5	×Mn
Breakdown torque	2.7	×Mn
Efficiency	67.8 64.3 55.2	IE1 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.78	@ 100% load

Mechanical data		
Bearings brand	C&U Customizable	(Standard) (Optional)
Bearings type	6201 2RZ C3 6201 2RZ C3	(DE) (NDE)
Lifetime of bearings		20000 hours
Allowed radial load	327 N	
Allowed axial load	260 N	
Grease type		
Lubrication interval of NDE bearing	h	
Lubrication interval of DE bearing	h	
Moment of inertia	0.000171	Kg*m²
Noise level	61	dB(A)